

ALUMINIUM SHUTTERS MAINTENANCE PROGRAM

The Weatherwell Aluminium Shutter Collection is perfectly situated to bring indoor and outdoor spaces closer together. Strong, durable and secure. Weatherwell shutters are specifically designed to weather the elements.

As a rule, stainless steel hardware and fittings are used to resist rust and corrosion, particularly in coastal atmospheres and applications. However, as for all quality products, cleanliness is essential for maximum resistance to corrosion.

CLEANING WEATHERWELL ALUMINIUM SHUTTERS

- Step 1** Clean the shutters using a nonabrasive cloth or sponge with warm soapy water. A garden hose may also be used. Concentrate on the areas where the stainless steel hardware is attached to the shutter.
- Step 2** Make sure to remove any salt residue, tannin stains caused by trees and any other marks created by local industry / automotive exhaust residue, as these chemicals also have corrosive properties.
- Step 3** On completion of the cleaning process, spray a light film of silicone lubricant to any operational hardware such as the tracking system. Please ensure these areas are fully dry prior to this application

It is recommended cleaning your aluminium shutters on a routine basis every six months

COASTAL AREA RECOMMENDATIONS

PROXIMITY	CLEANING TIME FRAME
Direct beach front	Weekly
1 km radius	Monthly
10km radius	Quarterly

OVERVIEW

By following these simple cleaning guidelines, possible corrosion of components can be avoided and the beauty, flexibility and durability of Weatherwell shutters can be fully enjoyed and appreciated.

Maintenance information was supplied by TWO Australia Manufacturer of Weatherwell.

For more information see TWO Australia web site (www.two-australia.com) for information concerning manufacturer's warranty and maintenance requirements

